



Fig. 398: Rear Door Trim Remove/Install Components
 Courtesy of VOLKSWAGEN UNITED STATES, INC.

1 - Door trim

• **Removing**

- Use a screwdriver to pry out treble speaker panel - **3** -.
- Remove screw - **2** -.
- Remove screw - **5** -.

Do not open hinged pocket - **6** -.

- With sun shade: Remove decorative panel --> **Trim Molding, Removing and Installing**.
- Remove the bolts - **4** -.

2007 Audi S8 Quattro

ACCESSORIES & EQUIPMENT Body Interior - A8 & S8

- Unclip door trim - **1** - starting from below at clips - **7** - (8x).
- Disengage release for interior door mechanism --> **Disengage release**
- Disconnect harness connector on window regulator control module --> **Disconnecting harness connector at window regulator control module.**
- Disconnect harness connector on bass speaker --> **Disconnecting harness connector on bass speaker.**

● **Installing**

- Make sure that all clips - **7** - on rear side of door trim are clipped in. Replace damaged clips --> **Door trim securing clip.**
- Install door trim - **1** - in reverse order of removal.

2 - Screw

- A nut is installed on vehicles with long wheel base.
- Tightening torque 3 Nm.

3 - Treble speaker panel

4 - Bolts

- 4 bolts are installed on vehicles with long wheel base.
- Tightening torque 3 Nm.

5 - Screw

- A nut is installed on vehicles with long wheel base.
- Tightening torque 3 Nm.

6 - Hinged pocket with mount

7 - Clips (8x)

8 - Door shell

Disengage release