



2008 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105/125/145 165/185/205/225/245/265	15/55/95/135/175 215/255/295/335	35/75/115/155 195/235/275
Engine Oil – change oil and replace filter	●	●	●
Wiper Blades – check condition and replace if necessary	●	●	●
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	●	●	●
Tires and Spare – check for wear and damage, check pressure – check for wear and damage, check pressure and renewal date of tire set (where applicable)	●	●	●
Tires – rotate	● 5K only		
Service Reminder Display – reset	●	●	●
Brake System – check for damage, leaks, pad thickness, fluid level	●	●	●
Cooling System – check level, add if necessary		●	●
Exhaust System – check for damage, leaks		●	●
Engine On-Board Diagnostics – check fault memory		● Except Audi Q7, TT, A5, S5 and R8	● Except Audi Q7, TT, A5, S5 and R8
Engine Compartment – check for leaks		●	●
Battery – check and replace if necessary		●	●
Dust and Pollen Filter – replace		●	●
Automatic Transmission and Final Drive – check for leaks		●	●
Manual Transmission and Final Drive – check for leaks		●	●
Haldex Clutch – change oil			● A3 and TT only
Front Axle – check for excessive play, check dust seals on ball joints and tie rod ends		● Except Audi Q7, TT, A5, S5 and R8	●
Lights – check all lights, check headlight adjustment		● A8 and S8 only	● Except Audi Q7, TT, R8, A5 and S5
Drive Shaft Boots – check		●	●
Front Sunroof Drains (where applicable) – open sunroof to check front water drain and clean if necessary (U.S. only)			●
Plenum Panel – remove cover to plenum panel to check water drains and clean if necessary (U.S. only)			● A4, A4 Avant, A4 Cabriolet, S4, S4 Avant, S4 Cabriolet, RS4, RS4 Cabriolet, A6, A6 Avant, S6, A8 and S8 only
Doors – lubricate doors, check straps and hood latch		● A8 and S8 only	●
Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first. Then, every 40,000 miles or 3 years, whichever occurs first. – replace at 55,000 miles or 6 years, whichever occurs first. Then, every 60,000 miles or 6 years, whichever occurs first. – replace at 75,000 miles		● Except A3 3.2L, TT 3.2L and A8 6.0L	● 35K only: A3 3.2L, TT 3.2L and A8 6.0L ● 75K only: A3 3.2L, TT 3.2L and A8 6.0L
Continuously Variable Transmission (multitronic) – change ATF			●
Power Steering Fluid – check, add if necessary			●
Air Cleaner – clean housing, replace filter element		● 55K only: except RS4, Audi Q7 4.2L and A8 6.0L	● 35K only: RS4, A8 6.0L; 75K only: RS4, Audi Q7 4.2L and A8 6.0L
Ribbed V Belt and Tensioner – check condition and replace if necessary		● RS4 and R8 only	● RS4, Audi Q7 3.6L, A8 6.0L and R8 only
Ribbed V Belt – replace – check condition and replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary.			● 75K only: S4 ● 75K only: 2.0L, 3.2L, 4.2L FSI and 5.2L
Snow Screen for Air Cleaner – clean		● A4, A5, S5 and A6 only	● A4, A5, S5 and A6 only
Underbody – check for damage and leaks		●	●
Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air conditioning, ASL Automatic Shift Lock and power accessories		●	●
Rear Lid Hinges – lubricate		● A8 and S8 only	● A8 and S8 only
Horn – check function		●	●
Brake Discs – check thickness			●
Lights – check all lights via instrument cluster. Check license plate light from the rear of the vehicle			● Audi Q7, TT, A5, S5 and R8 only
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			●
S Tronic – change oil and replace filter element			● A3 and TT only
Brake Fluid – replace every 2 years regardless of mileage.			
Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A4 Cabriolet, S4 Cabriolet and RS 4 Cabriolet only).			

At 110K miles (175,000 km) replace timing belt (2.0L engine only). Check condition of timing belt tensioning system, dampening pulleys, and idler pulleys and replace if necessary (2.0L engine only).
 Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.