

Audi > C4 > 1992 - 1998 Body Exterior, Interior 63 - Bumpers

Rear bumper assembly, removing and installing (wagon)



- 1 -Bolt w/washer
- * 23 ± 2.0 Nm (17 ft lb ± 18 in lb)
- 2 -Washer
- 3 -Impact absorber
- 4 -Spacer



5 -Bumper w/cover


Removing:

- Unlock rear loading floor panel and fold up
- Remove screws -15- on both sides
- Remove luggage compartment trim -14- from both sides
- Remove screws -13- on both sides
- Remove screws for securing bumper to wheel housing => Fig. 1
- Unclip bumper from guide pieces (both sides) -10-
- Push bumper down at ends => Fig. 2, and pull out of guide pieces -10-
- Remove bumper from both ends when taking off
- Pull bumper off toward rear

To install:

Install in reverse order of removal, noting the following:

- Guide bumper into guide pieces from bottom (reverse of Fig. 2)
- Clip bumper ends into guide pieces



6 -Trim strip, right

Removing => Fig. 3

7 -Trim strip, center

- Removing => Fig. 3

8 -Trim strip, left

Removing => Fig. 3

9 -Screw w/washer

◆ 1.5 ± 0.2 Nm (13 ± 1.77 in lb)

10 -Guide pieces, left/right

11 -Expanding nut

12 -Nut

* 2.5 ± 0.5 Nm (22 ± 4.4 in lb)

13 -Bolt w/washer

- * 15 ± 1.5 Nm (11 ± 13 in lb)
- * M10 x 95

14 -Luggage compartment trim, left/center/right

15 -Self-tapping screw w/washer




Fig. 1 Removing and installing bumper to wheel housing liner

Removing

- Remove Phillips screws -16-, -17-.

Installing

Install in reverse order of removal.




Fig. 2 Removing bumper from guide pieces

Unclip bumper in direction of arrow -A-.




Fig. 3 Removing and installing bumper trim strips

Removing

- Cover bumper at trim strip mounting clip location points to protect from damage.

Note:

Trim strips cannot be removed without destroying them. Always replace.

- Using plastic putty knife, pry off trim strips, as shown.

Installing

Install in reverse order of removal.