

## Audi of America Audi A5 Cabriolet 2.0 TFSI Technical Specifications 2010 Model Year

Technical Specifications			2010 Audi A5 Cabriolet 2.0 TFS																
ENGINE:																			
Туре	Inline four-cylinde	r gasoline engine with FSI direct injection, exhaust turbo	charger with intercooler, four valves per cylinder.																
Arrangement	Front mounted, longitudinal																		
Bore	3.25 in.	82.5 mm																	
Stroke	3.65 in.	92.8 mm																	
Displacement	· · · · · · · · · · · · · · · · · · ·	1984 CC																	
Compression ratio	<u>}</u>																		
Fuel requirement																			
Horsepower (SAE)	211 hp	@ 4300-6000 rpm																	
Max. Torque	258 lbs. ft.	@ 1500-4200 rpm																	
ENGINE DESIGN:																			
Cylinder block	cast iron																		
Cylinder head	aluminum alloy	aluminum alloy																	
Valve train / intake	·····	em on exhaust valves. DOHC. chain driven. hvdraulic lift	ers																
Firing order	<	cast iron aluminum alloy Audi valvelit system on exhaust valves. DOHC, chain driven, hydraulic lifters 1-3.4-2 Electronic engine management, drive-by-wire throttle, FSI direct injection Close-coupled ceramic catalytic converter EUS; ULEVII  12 volts 60 amp/hr 14 volts 140 amp  Automatic: Multitronic Continuously variable transmission (CVT)  Tiptronic automatic (quattro AWD) Automatic: 156 1464 215 1464 215 1464 215 1464 215 1464 215 1464 215 215 258 26404 25 21 20 20 21 20 20 21 20 20 20 20 20 20 20 20 20 20 20 20 20										\							
Fuel injection	·····	management drive-by-wire throttle FSI direct injection																	
Emission system																			
Emissions level	EU5; ULEVII																		
ELECTRICAL SYSTEM:																			
Battery	12 volts	60 amp/hr																	
Alternator	14 volts	140 amp																	
DRIVETRAIN:																			
Transmission	Automatic: Tintro	nic 6 speed automatic																	
Tanamasion																			
Turne	Automatic. Wultit																		
Туре																			
Gear ratios: 1st																			
2nd																			
3rd		1.464	1.140																
4th		1.079	0.885																
5th		1.094	0.701																
6th		0.921																	
7th		-																	
8th		-																	
reverse		3 989																	
Final Drive																			
Front Differential	alectronically look	5.115																	
	,																		
Center Differential (for quattro)	(																		
Rear Differential (for quattro)		ing (EDL)																	
STEERING:																			
Туре	Servotronic vehic	e speed-sensitive hydraulic power assist																	
Ratio	16.3:1	······																	
	{																		
Turning circle (curb-to-curb)	37.4 ft.	11.4 m																	
SUSPENSION:																			
Front	Five-link front sus	pension, upper and lower wishbones, tubular anti-roll ba	r																
Rear	·····	ezoidal link with resiliently mounted subframe, anti-roll ba																	
	,																		
BRAKES:																			
System	Dual-circuit brake system with diagonal split, Anti-lock Brake System (ABS), Electronic Brake pressure Distribution (EBD)																		
	and Electronic St	abilization Program (ESP); tandem brake booster																	
Front																			
Front	Ventilated discs	12.6 in. (320 mm)																	
Rear	Solid discs	11.8 in. (300 mm)																	
	1																		


## Audi of America Audi A5 Cabriolet 2.0 TFSI Technical Specifications 2010 Model Year

Technical Specifi	cations (continu	ied)								201	0 Audi A5 Cabriolet 2.0
WHEELS:											
Size		8.5X18 alloy				standar					
		8.5X19 alloy				optional	l				
TIRES:											
		245/40 D40 all				atandar					
Size		245/40 R18 all season 255/35 R19 summer performance				standar					
		255/55 K 19 Sul	niner periornance		optional						
BODY:											
Material		I Initized atool of	tructure; Cloth conv	vortible r	oof						
Corrosion protection						ar limited warranty	against corros	ion porfor	ation)		
VARRANTY/MAINTEN		All steel parts are 100% dual-side zinc-galvanized (12 year limited warranty against corrosion perforation)									
	ANCE.	4-Year/50,000 mile new vehicle limited warranty 12-Month/5,000 mile (whichever occurs first)									
		12-1001111/0,000			, , , , , , , , , , , , , , , , , , ,						
CAPACITIES:											
Engine oil		4.86 qt.	4.6 liter								
Fuel tank		17.17 gal.	65 liter								
Cooling system		7.4 qt.	7 liter								
EXTERIOR DIMENSIO	NS:										
Wheelbase		108.3 in.	2751 mm								
Track:	front / rear	62.6/62.1	1590/1577								
Overall length		182.1 in.	4625 mm								
Overall width	incl. mirrors	79.5 in.	2020 mm								
Height (unloaded)		54.4 in.	1383 mm								
Ground clearance (lo	oaded)	n/a in.	n/a mm								
		Fron	tTrak Multitronic		qua	attro Tiptronic					
Curb weight		3880	lbs		4034	lbs					
Drag coefficient		Cd = 0.31	Frontal Area =	=	2.18 sq. m.						
NTERIOR DIMENSION	NS:										
EPA Class		Subcompact ca	rs								
Seating Capacity		4									
Head room	front / rear	39.9 in.	1014 mm	1	36.3 in.	922 mm					
Leg room	front / rear	41.34 in.	1050 mm	1	31.9 in.	810.26 mm					
Shoulder room	front / rear	54.3 in.	1378 mm		46.9 in.	1190 mm					
Int. vol. (EPA)		n/a cu. ft.									
Luggage capacity (E	:PA)	10.2 cu. ft.									
PERFORMANCE:											
			o Tiptronic Trans						ronic Trans		
0-60 mph		7.2 sec. Electronically limited to 130 mph						7.5	sec.	i	
Top speed		Electronically lin	nited to 130 mpn								
UEL ECONOMY:											
		guatti	o Tiptronic Trans					Multitr	ronic Trans		
City		20	mpg					23	mpg		
Highway		26	mpg					30	mpg		
Combined		23	mpg					26	mpg		

## Audi A5 Cabriolet



Dimensions 02/09



Dimensions of vehicle unloaded