2012 Audi S4 Technical specifications




Technical specifi	cations		2012 Audi S4		
ENGINE:					
Туре		Direct petrol injection supercharged V6 with variable intake manifold, continuou	us camshaft adjustment. DOHC		
Arrangement		Front mounted, longitudinal	······································		
Bore		3.33 in 84.5 mm			
Stroke		3.50 in 89 mm			
Displacement		182.6 cu in 2995 cc			
Compression ratio					
Fuel requirement		Premium unleaded (91 Octane) recommended			
Horsepower (SAE)		333 hp @ 5,500 245 kW			
Max. torque		325 lb ft @ 2,900 440 nm			
ENGINE DESIGN:					
Cylinder block		Aluminum alloy			
Cylinder head		Aluminum alloy			
Valve train / intake		DOHC, mechanical charger module with two intercoolers, two charge movement flaps, chain driven, four valves per cylinder			
Supercharger		Eaton R1320, maximum boost: 0.8 BAR / 11.6 psi			
Firing order		1 4 - 3 - 6 - 2 - 5			
Fuel injection /		Fully electronic engine management with drive-by-wire throttle control, direct petrol injection, cylinder selective lambda control			
Ignition system		Mapped ignition with solid-state high-voltage distribution, manifold-pressure controlled system			
Emission system		Mapped ignition with solid-state nigh-voltage distribution, manifold-pressure controlled system Dual close-coupled ceramic main catalytic converters			
Emission system Emissions level		Tier2 BIN5 / ULEV II			
ELECTRICAL SYSTEM					
Battery	vi.	12 volts 80 amp/hr			
Alternator		14 volts 140 amp			
DRIVETRAIN:					
Transmission		Automatic: S tronic® seven-speed dual clutch			
rianomiooion		Manual: six-speed			
Туре		quattro® S tronic	quattro manual		
Type		dual electro-hyrdraulic clutch	manual, hydraulic clutch		
Gear ratios:	1st	3.692	3.667		
Gear ratios.	2nd	2.238	2.158		
	3rd	1.559	1.520		
	4th	1.175	1.133		
	5th	0.915	0.919		
	6th	0.745	0.778		
	7th	0.745	0.778		
Front differential			0.000		
	Reverse Final drive	2.944 3.875	<u>3.222</u> 3.682		
	Final Unve		3.002		
Front differential		Hypoid gear, electronically locking (EDL)			
Center differential		Self-locking differential providing automatic and variable front to rear power proportioning			
Rear differential		Hypoid gear, electronically locking (EDL), optional mechanical torque-vectoring	y		
STEERING:					
Туре		Vehicle speed-sensitive power rack and pinion, maintenance-free			
Ratio		16.3:1			
Turning circle (curb-	to-curb)	37.4 ft 11.4 m			
SUSPENSION:					
Front		Five-link front suspension, upper and lower wishbones, tubular anti-roll bar			
Rear		Independent trapezoidal link with resiliently mounted subframe, anti-roll bar			
BRAKES:					
System		Dual-circuit brake system with diagonal split, Anti-lock brake system (ABS), Electronic Brake pressure Distribution (EBD)			
		and Electronic Stabilization Program (ESP); tandem brake booster			
Front		13.6 in 345 mm - Ventilated disc			
Rear		13.0 in 330 mm - Ventilated disc			
Parking brake					

Technical specifications	(continued)		2012 Audi S4	
WHEELS:				
Size		8.0J x 18, five-parallel-spoke-S-design standard		
		8.5J x 19, five-segment-spoke-design optional		
		8.5J x 19, five-arm-Rotor-design, Titanium finish optional		
TIRES:				
Size		245/40 R18 summer tires standard		
		255/35 R19 summer tires optional		
BODY:				
Material		Unitized steel structure with integrated aluminum and magnesium components		
Corrosion protection		All steel parts are 100% dual-side zinc-galvanized (twelve-year limited warranty against corrosion perforation)		
WARRANTY/MAINTENANCE:				
		Four-year/50,000 mile new vehicle limited warranty		
		Twelve-month/5,000 mile (whichever occurs first)		
CAPACITIES:				
Engine oil		8.6 qt 8.1 liter		
Fuel tank		16.9 gal 64 liter		
EXTERIOR DIMENSIONS:				
		Sedan		
Wheelbase		110.7 in 2811 mm		
Track:	front / rear	61.1 / 60.6 1552 / 1539		
Overall length		185.7 in 4717 mm		
Overall width	mirrors	71.9 / 80.3 1826 / 2040		
Height (unloaded)		55.4 in 1406 mm		
Ground clearance (loaded)		n/a in n/a mm		
Curb weight		3,847 lb 1745 kg 3,924 lb 1780 kg (Stronic)		
Drag coefficient		Cw = 0.29 Frontal Area = = 2.20 sq m		
INTERIOR DIMENSIONS:		1		
EPA class		Compact class		
Seating capacity		Five		
		Sedan		
Headroom (sunroof)	front / rear	40.0 in 1016 mm / 37.5 in 953 mm		
w/ sunshade	front / rear	38.6 in 980 mm / 37.5 in 953 mm		
Shoulder room	front / rear	55.5 in 1410 mm / 54.3 in 1379 mm		
Leg room	front / rear	41.3 in 1049 mm / 35.2 in 894 mm		
Int. vol. (EPA)				
Luggage capacity (EPA)		12.4 cu ft 34.0 cu ft (2nd row folded)		
PERFORMANCE:		1		
		quattro S tronic quattro manual		
0-60 mph		4.9 sec 4.9 sec		
Top speed		Electronically limited to 155 mph		
FUEL ECONOMY:		2012 EPA figures		
		quattro S tronic quattro manual		
City		18 mpg 18 mpg		
Highway		28 mpg 27 mpg		
Combined		21 mpg 21 mpg		
			·	



Audi S4

Dimensions



maximum headroom
 Dimensions in milimeters and inches
 Dimensions of vehicle unloaded