## 2012 Audi TT RS Technical specifications



Technical specification	tions	2012 Audi TT RS six-speed manual quat			
NGINE:					
Туре		2.5 liter turbocharged, in-line five-cylinder, spark-ignition engine with TFSI® direct injection, four valves per cylinder, double overhead camshafts [DOHC], turbocharger with intercooler			
Arrangement		Front mounted, transverse			
Bore		- 1011 mounted, answerse 3.25 in 82.5 mm			
Stroke		3.65 in 92.8 mm			
Displacement		151/3.25/3.65 2480/26.5×92.8			
Compression ratio		10.01			
		Unleaded Super, 95 RON (unleaded regular, 91 RON, as an alternative with slight reduction in performance)			
Fuel requirement		360 hp @ 5,500 - 6,700 rpm 265 kW			
Horsepower (SAE) Max. torque		343 lb-ft @ 1,650 - 5,400 rpm 465 Nm			
NGINE DESIGN:		345 10-10 W 1,000 - 3,400 10111 403 1011			
Cylinder block		Cast iron			
-					
Crankshaft		Aluminum			
Cylinder head					
Valve train / intake		DOHC, four valves/cyliinder			
Firing order					
Lubrication system Fuel injection / Ignition system					
Emission system					
LECTRICAL SYSTEM:					
		380 amp 80 amp/hr			
Battery Alternator		140 amp			
RIVETRAIN:		i tav anip			
Transmission		Six-speed manual, fully synchronized			
Туре					
Gear ratios:	1st	3,570			
ocul rulos.	2nd	2.160			
	3rd	1.890			
	4th	1.330 1.430			
	5th	1.160			
	6th	0.097			
	Reverse	4.500			
Front differential	Reverse	4:500			
Center differential					
Rear differential					
EERING:					
		Eletromechanical steering with speed-dependent power assistance			
Type Ratio		Lieu Uniculari steering with speed-dependent power assistance 16.9 : 1			
		2.9			
Turns (lock-to-lock)					
Turning circle (curb-to- JSPENSION:	-curb)	35.96 ft 10.96 m			
JOPENOION.					
Front					
Front Rear		Mac Pherson strut (gas charged) with aluminum three-point lower control arm, aluminum sub frame, tubular anti-roll bar, track-stabilizing steering roll radius			
RAKES:		Four-link rear suspension with separate spring/shock absorber arrangement, sub frame, aluminum wheel mounts, tubular anti-roll bar			
Service brake		Dual-circuit brake system with diagonal split, ESP, hydraulic brake assistant, front and rear disc brakes ventilated			
		14.6 in 370 mm			
Front size		14.6 in 370 mm 12.2 in 310 mm			
Rear size		12.2 in 310 mm			

Technical specifications (	cont.)	1
----------------------------	--------	---


2012 Audi TT RS six-speed manual quattro

lechnical specifications (	(cont.)		2012	Audi 11 RS six-speed manual quattro	
WHEELS (standard only):		-			
Size		Aluminum, 9Jx19			
TIRES (standard only):					
Size		255/35 R19 Y			
BODY:					
Material		Audi ASF® space frame: Lightweight construction concept which is a mixed construction using aluminium and steel			
Corrosion protection		Multi-step anti-corrosion protection			
CAPACITIES:					
Engine oil		6.9 qt	6.5 liter		
Fuel tank		15.90 gal	60 liter		
EXTERIOR DIMENSIONS:					
Wheelbase		97.2 in	2,468 mm		
Track front / rear		61.2/ 60.9 in	1,555/ 1,546 mm		
Overall length		165.3 in	4,198 mm		
Overall width w/o mirrors		72.5 in	1,842 mm		
Height		53.1 in	1,348 mm		
Curb weight: quattro	Curb weight: quattro		1500 kg		
Distribution front / rear [%]					
Drag coefficient		TT RS Coupe: 0.32			
INTERIOR DIMENSIONS:					
Seating capacity		2 + 2			
Head room	front / rear	37.7/ 32.6 in	957/ 829 mm		
Shoulder room	front / rear	53.2/ 47.5 in	1,352/ 1,206 mm		
Leg room	front / rear	41.1/ 29.3 in	1,044/ 743 mm		
Int. vol. (EPA)	front / rear	47.7/ 26.2 cu ft			
Luggage capacity	std / seats folded	13.1/ 24.7 cu ft	290/ 700 Liters		
PERFORMANCE:					
0-60 mph		4.1			
1/4 mile		n/a			
Top speed		174			
EFFICIENCY/ENVIRONMENT:					
Emission class					
		EPA estimate			
City		mpg	Not available at present time		
Highway		mpg	Not available at present time		
Combined		mpg	Not available at present time		

## Audi TT RS Coupe



Dimensions



\* maximum headroom Dimensions in milimeters and inches Dimensions of vehicle unloaded